



**Marine Engine Warning Kit**

Protects engines from the two major causes of damage: no lubrication and overheating. Handy kit includes buzzer, temperature switch and low oil pressure switch. Buzzer sounds when oil pressure is too low and/or the engine coolant temperature is too high. Pressure switch operates at 6 psi; temperature switch operates at 200° F (93.3°C). Installation instructions are included.

- For inboard and I/O engines
- Buzzer is constructed from impact-resistant ABS resin, and has moisture-resistant insulator
- For use with 12V DC systems



ORDER NO.	DESCRIPTION	PRICE
COL M40177BP	Kit Complete	\$54.40
COL M4099	Replacement Buzzer	\$20.95



**Engine Warning System**

Audible warning system for engine temperature and pressure. Loud warning buzzer makes certain the operator is warned of dangerously high engine temperatures or low engine oil pressure. Kit includes instructions, oil pressure switch (set at 6 PSI) and temperature switch (set at 200°F).



ORDER NO.	PRICE
SIE MP41400	\$49.99



**Fume, Fire and Flood Detector**

Marine Operating Specifications

- Easy, snap together assembly.
- Marine environment tested for salt water spray, shock, temperature extremes, vibration and corrosion.
- Power 12 vDC, operational range 7-16 volts.
- 200 milliamp (.2 amp.) current draw.
- Fumes Detected: Gasoline, hydrogen from batteries, propane, alcohol, acetone, methane and other explosive vapors.
- Fire Alarm Trigger: 180° Thermal Switch.
- Flood sensor triggers during high bilge water conditions.
- On/Off/Test Switch. For one touch analysis of detector performance.
- Size: 3-1/4"W x 2-3/4"H x 3/4"D.



ORDER NO.	PRICE
MTI SA10XL	\$336.25



**Smoke Alarm**

Features Include:

- Alarm Mute with Auto Reset - Used to temporarily silence alarm during ventilation. Detector automatically resets.
- 5 Year Limited Warranty.
- Easy to install - No wiring required.
- 24 hour continuous protection.
- Low battery signal.
- Safe ionization technology.
- Micro design and engineered.
- Battery operated - 9 volt battery included.
- Suitable for use in recreational vehicle.



ORDER NO.	PRICE
MTI SA668M	\$14.38



**Advantages At A Glance - M-2A-R 2-Channel Gasoline Fume Detector**

Two-channel monitoring capability in a low profile, water resistant design 4 3/4" by 3 3/4" by 7/8". Features include: 50% less current draw, plug-in splash proof sensor/s (second sensor optional), display module "Fault" light alarm and separate sensor/s fault light. (Fault indicators let you know the module or sensor/s are not working and may need repair.) Press to test for each sensor channel confirms function. Alarm silence button deactivates alarm horn. The M-2A sensors are calibrated to provide both a visual and audible alarm should fume buildup reach 18% to 20% LEL (Lower Explosive Limit). This alarm level is high enough to eliminate most nuisance alarms but low enough to allow some time to take action.



ORDER NO.	PRICE
FRB M2AR	\$393.28