

MARINE TECHNOLOGIES INC.

Carbon Monoxide Alarms

- Memory Scan™. Retains the CO level that activated the alarm.
- Fully Operational During Mute. Mute does not override detection circuit, giving you full time protection.
- Micro Current Technology. Saves precious battery power.
- Two Level Alarm - Caution and Hazardous. Caution notifies you of moderate (60ppm) levels of CO, helps protect high risk groups, seniors and children.
- Long Life, Self Cleaning Sensor. Maintenance free sensor. No need to replace every 2 or 3 years.
- Loud 85 dB Alarm. Alerts you to CO danger.
- Test/Reset Button. Used to temporarily silence alarm during ventilation. Tests all detector functions and activates Memory Scan.



ORDER NO.	DESCRIPTION	PRICE
MTI 60541	Surface Mount	\$94.75
MTI 60542	Flush Mount	\$94.75

XINTEX Carbon Monoxide Detector

Multiple Location Warning

- When one CO Sentinel alarms, all connected CO Sentinel alarms sound

Low Battery Current Draw

- Extremely low current draw permits direct battery connection without discharge

Stylish and Sleek Design

- Takes up less wall space with its low profile design

Quality and Reliability Built-in

- Listed to UL 2034 rigid Marine Standards
- Microprocessor controlled
- Conformal coated board on both sides, provides added protection from the harsh marine environment
- Our time-weighted average CO measurement process constantly monitors all CO levels eliminating most false alarms
- State of the art sensor is not affected by common cleaning solvents



ORDER NO.	DESCRIPTION	PRICE
FRB CMD4MR	CO Detector	\$156.95

XINTEX

Gasoline Fume Detector

An ideal single channel gasoline fume detector, featuring high-tech styling, compact size, circuitry test and alarm horn Mute functions. The power on indicator lamp automatically increases in brightness during daylight and softens at night. Includes a standard two-inch display unit with gasoline sensor and twenty feet of plug-together lead. It can also detect high concentrations of battery hydrogen or engine exhaust. Installation is quick and simple.



The MB-1-R adds a 10 amp relay to automatically start the bilge blower fan should gasoline fumes be detected. Installation requires only the addition of two wire leads from the control to the blower switch.

ORDER NO.	DESCRIPTION	PRICE
FRB M1R	Gasoline Fume Detector	\$224.14
FRB MB1R	Gasoline Fume Detector w/ Auto Bilge Control	\$267.62

XINTEX

9V Marine Carbon Monoxide Alarm

- Time Weighted Average sensor technology – advanced CO monitoring technology
- Patented biomimetic sensor mimics the human response to carbon monoxide
- Sensor is not affected by common cleaning solvents
- Listed to UL 2034 rigid marine standards
- Ceiling or wall mount
- Install one CO alarm in every sleeping area, galley, and confined space for adequate protection
- Ideal for all boats requiring additional CO alarm protection and for boats without a CO alarm
- Dimensions: 4-3/4" diameter x 1-1/2" height
- 1 year limited warranty
- Uses 9V Battery



ORDER NO.	PRICE
FRB CMD1MR9V	\$146.38

XINTEX MS-2 Gasoline and Propane Sensor

Red, with quick disconnect 12" lead, and standard sensor cable 20' for use with M-1-R, MB-1-R, M-2A-R, MB-2-R, S-1, S-1A, S-2A. (Replaces MS-1 and PS-1).



ORDER NO.	PRICE
FRB XMS2	\$95.95

MARINE TECHNOLOGIES INC.

Gasoline Fume Detectors

Marine Operating Specifications

- Easy, snap together assembly.
- UL listed to Marine Combustible Gas Indicators UL 1110.
- Power 12 vDC, operational range 7-16 volts.
- 200 milliamp (.2 amp.) current draw.
- Alarm Trigger: 20% or less of the lower explosive limit of gasoline.
- Fumes Detected: Gasoline, hydrogen from batteries, propane, alcohol, acetone, methane and other explosive vapors.
- On/Off/Test Switch. For one touch analysis of detector performance.
- Size: SA-1 fits standard 2 1/8" in dash panel blank.
SA-1XL: 3 1/4"W x 2 3/4"H x 3/4"D.

ORDER NO.	DESCRIPTION	PRICE
MTI SA1	Dash Mount 2-1/8"	\$185.75
MTI SA1XL	Surface Mount	\$185.75



MTI SA1