



F2 Trailer Jacks
1,600 lbs. Lift Capacity

Precision extruded aluminum alloy inner & outer tubes, combined with twin alignment bushings, ensure a precision alignment. The anodized finish keep the tubes virtually corrosion free. Revolutionary adjustable mount & swivel system. Engineered to be the strongest swivel mechanism in the industry, it is also the first mounting system that can be adjusted to any desired height. Integrated pull pin with ergonomic grip makes it easy to swivel into position for lifting or transport. Smooth wheel performance. Twin track 7" diameter wheels are designed to roll independently to make changing direction smooth and effortless. 5-1/2" wide wheel base adds superior stability



- 8" of mount travel
- 10" of screw travel Total 18" of overall travel
- Fits bolt on 3" and 4" tongues
- Fits weld on 3" and up

| ORDER NO. | DESCRIPTION | PRICE |
|----------------|--------------------------|----------|
| FUL 1413020134 | Twin track 7" wide | \$142.17 |
| FUL 1413040134 | Single track 5-1/2" wide | \$142.17 |

Swivel Tongue Jack

- Screw type, swivel side mount
- 800 lb. capacity
- 10" travel
- 24-1/4" max. tongue height
- 3" x 5" max. tongue size



| ORDER NO. | PRICE |
|-----------|---------|
| DUT 3400 | \$59.00 |

Swivel Tongue Jack—Value Series

- (Some assembly required.)
- Screw type, swivel side mount
 - 800 lb. capacity
 - 10" travel
 - 24-1/4" max. tongue height
 - 3" x 5" max. tongue size
 - Some assembly required



| ORDER NO. | PRICE |
|-----------|---------|
| DUT 2400 | \$49.25 |

FULTON F2 Trailer Jack w/Footplate
2000 lbs. Lift Capacity



- Heavy Duty Articulating Footplate - 7" diameter cast footplate provides superior stability
- Unique ball and socket connection between jack and footplate allows for whatever articulation is required to accommodate uneven surfaces.
- 13" of swivel mount height adjustment
- Available in bolt-on versions for 4" and 5" frames and weld-on versions for up to 5" frames.
- Available in bolt-on versions for 3"x3" and 3"x4" tongues and weld-on versions for up to 3"x5" tongues
- LIMITED LIFETIME WARRANTY



| ORDER NO. | PRICE |
|----------------|----------|
| FUL 1413230134 | \$163.58 |

6400 Pivoting Tongue Jack

Pivoting, screw type tongue jack has an 1000 lb. tongue weight capacity. Jack operates on a precision rolled Acme thread which is an extra heavy duty screw type drive. Comes complete with all necessary hardware for mounting. Zinc-plated with TUFFPLATE® finish. Fits square tongues up to 3" x 5".



| ORDER NO. | PRICE |
|-----------|---------|
| DUT 6400A | \$74.63 |

Pivoting Tongue Jack

Pivoting screw-type tongue jacks are easily rotated to a vertical use position and reduce cranking to a minimum. The jack can be rotated to a towing position by operating the spring-loaded locking mechanism.

- Totally enclosed outer tube retards sand and dirt from coming in contact with miter gears and heavy duty Acme screw
- All necessary mounting hardware included. Fits square tongues up to 3" x 5". Can be adapted for round tongue mounting.
- Floating miter gears allow for proper clearance resulting in easier operation
- Extra lift for high mounted bumper applications.
- All bright zinc plated TUFFPLATE® finish for longer life
- Maximum maneuverability from offset swivel caster assembly
- 1000 lb. capacity, 12" travel
- Made in U.S.A.



| ORDER NO. | PRICE |
|-----------|----------|
| DUT 6709 | \$100.86 |

Pivoting Screw-type Tongue Jack

Easily rotated to a vertical use position and reduce cranking to a minimum. The jack can be rotated to a towing position by operating the spring-loaded locking mechanism. Standard pack is four-bolt mounting system unassembled. 1500 pound tongue weight capacity, zinc-plated TUFFPLATE® finish and tough polypropylene wheel. Maximum tongue height 28-1/2". Maximum tongue size 3" x 5".



| ORDER NO. | DESCRIPTION | PRICE |
|-----------|-------------|----------|
| DUT 6800A | 12" Travel | \$140.35 |

FULTON Retaining Ring Swivel Marine Jacks



Zinc, with 1000 lbs. lift capacity and a 6" diameter caster. Designed for use with marine and utility trailers. Includes all necessary mounting hardware. Fits up to a 3" x 5" trailer frame.

Overall Length: Retracted 12.8"
Extended 22.8"



| ORDER NO. | DESCRIPTION | PRICE |
|----------------|-------------|---------|
| FUL EJ10000101 | Boxed | \$46.09 |
| FUL EJ10000301 | Bulk | \$43.77 |



Swivel Jack – 800 Lb. Capacity

Heavy duty zinc-plated steel tubing. Six inch (6") reinforced poly wheel (replaceable). Fits trailer frames up to 3" x 5". Includes all necessary mounting hardware.



| ORDER NO. | OVERALL LENGTH | | PRICE |
|---------------|----------------|----------|---------|
| | RETRACTED | EXTENDED | |
| FUL TJ5030101 | 12.75" | 22.75" | \$87.02 |