



**Manual/Automatic FM-200 Fire Extinguishing System**

USCG approved in sizes from 25 cubic feet up to 240 cubic feet of engine compartment volume. FG models feature light-weight compact corrosion resistant aluminum cylinders for easy fit and installation. All FG systems operate automatically through heat activation. However the boat operator has the option of pulling a discharge cable which activates the fire system.

FM-200 is the premier Halon replacement with worldwide acceptability. Provides non-toxic and non-corrosive protection. FM-200 is also non-ozone depleting. Clean gaseous vapor means no messy cleanup of powder or foam.

- Automatic discharge
- Pressure gauge
- Pressure switch
- Protective guard
- Mounting bracket
- Indicator light and bezel
- Installation, operation and maintenance manual



FG Models are non-refillable

ORDER NO.	MAX VOLUME PROTECTED	DIMENSIONS	GROSS WEIGHT	PRICE
SFR FG25M	25 cu.ft.	2.5" x 9"	3.2 lbs.	\$257.00
SFR FG75M	75 cu.ft.	3.1" x 15"	5.9 lbs.	\$403.00
SFR FG150M	150 cu.ft.	4.1" x 16"	11 lbs.	\$604.00



**Featuring FE-241 Extinguishing Agent**

- Clean agent (leaves no residue)
- For use in normally unoccupied areas only (i.e. boat engine compartments)
- U.S. EPA Accepted Halon Alternative

**All Models Include:**

- Automatic discharge (heat actuated)
- Pressure gauge
- Protective guard
- Mounting bracket
- Indicator light and bezel
- Installation, operation and maintenance manual
- Three year warranty

**Optional Equipment**

- Manual discharge capability
- Audible discharge alarm
- Engine shutdown/override system
- Manual discharge cable assembly



ORDER NO.	MAX VOLUME PROTECTED	DIA. X HEIGHT	WEIGHT	PRICE
SFR FE25M	25 cu. ft.	2.5" x 9"	3.0 lbs.	\$274.00
SFR FE75M	75 cu. ft.	3.1" x 15"	5.6 lbs.	\$363.00
SFR FE150M	150 cu. ft.	4.1" x 15"	15.0 lbs.	\$475.00
SFR FE200M	200 cu. ft.	5.1" x 16"	17.0 lbs.	\$544.00
SFR FE300M	300 cu. ft.	5.1" x 18"	27.0 lbs.	\$772.00
SFR FE400M	400 cu. ft.	6.3" x 17"	33.0 lbs.	\$1013.00
SFR FE500M	500 cu. ft.	7.1" x 18"	37.0 lbs.	\$1145.00



**CG2 Series Fire Extinguishers**

**Heat Activated Only System.** With the CG2 Series, heat-activated discharge is automatic at 175°F, 79°C. A control panel indicator lamp and pressure gauge provide "charge/discharge" system-status.

**WARNING: Diesel-powered craft must also install an Automatic Engine Shutdown System.**

- All systems USCG and FM approved.
- May be installed vertically or horizontally.
- USEPA accepted Halon alternative
- Wire head guard
- Complete with mounting brackets
- 3 year warranty
- Clean extinguishing agent, no residue!



ORDER NO.	MAXIMUM VOLUME PROTECTED	DIAMETER	HEIGHT	PRICE
FRB CG2025	25 cu. ft.	3"	9.1"	\$265.49
FRB CG2050	50 cu. ft.	3"	12.2"	\$297.43