



Automatic Multi-Outlet Water System Ultra-Max

Installation takes just minutes requiring only base mounting, two plumbing and two wire connections.

- Par-Max 4 pump self-priming to 5 ft., runs dry without damage and provides quiet, low amp draw operation.
- 1 liter accumulator tank smoothes flow, eliminates pulsation, and ensures even temperature mix at the faucet. Its bladder type design never needs recharging.
- Pumpguard strainer snaps directly into the Par-Max pump and is supported by a sturdy molded in leg. The stainless steel fine mesh screen can be removed in seconds without tools for easy maintenance.
- Motors are thermally protected, comply with USCG Electrical Regulations including ignition protection, ISO 8846 MARINE, and are CE marked. Ultra Max is supplied with both 1/2" Qest® threaded and 1/2" barbed inlet and outlet ports.
- Flow 3.8 GPM



ORDER NO.	PRICE
ITT 594511012	\$361.16



Par Max 1 WPS Pump

- Low flow WPS
- Ideal for small cruisers and runabouts
- 1.1 gallon per minute
- Self-priming – can be mounted above water tank
- Accepts 3/8" hose
- 12 volt



ORDER NO.	PRICE
ITT 426302900	\$72.23



Sensor-Max 14 and 17

Pressure sensor controlled, multi-outlet water pressure pumps, with variable speed drive, serve 1 - 5 outlets. Motor speed is electronically controlled to maintain steady flow and constant pressure. Sensor Max TM VSD accepts from 10 to 29 Volt DC for use with 12 or 24 Volt DC power. Amp draw reduces as flow reduces to conserve energy, ranging from less than 1 amp to a maximum of 10 amps.



ORDER NO.	MODEL #	GPM	PSI	PRICE
ITT 317500000	Sensor-Max 14	3.7	25	\$275.07
ITT 317550000	Sensor-Max 17	4.5	25	\$312.50



Par-Max 3 Shower Drain Pump

New Generation Par-Max3 livewell/shower drain pump. Self-priming up to 10' and is a 4 piston chamber design that delivers 3.5 GPM for smooth and quiet operation. Diaphragm design allows for extended dry running. Waterproof coated motor. Snap in 3/4" hose barb and strainer. 12 V DC.



ORDER NO.	PRICE
ITT 316100092	\$163.47



PAR MAX 4 Bilge/Livewell Pump

The PAR-MAX 4 bilge/livewell pumps offer big 3.8 GPM flow, run-dry ability in a compact, low profile design. Heavy duty motor has a special waterproof coating for harsh environment applications. Same high performance when used as an intermittent duty bilge pump or as a continuous duty livewell pump. Motors are thermal overload protected and meet USCG requirements including ignition protection. Includes 36200-0000 Pumpguard strainer. Dimensions - Height 4-1/16", Width 4-1/8", Length 7-1/4".



ORDER NO.	AMP DRAW	GPM/ LPM	VOLTS DC	PRICE
	@ 10 PSI			
ITT 317050092	7	4.3/16.3	12	\$216.97



Livewell/Washdown Pump System

Combination pack containing a PAR-Max Washdown pump, a Rule Dual-port livewell pump complete with Hose-Coil, 15' retractable hose, trigger nozzle and pumpguard strainer. 12 volt.



ORDER NO.	PRICE
ITT 319000020	\$347.82