



**Standard Utility Pump**

The Geolast Diaphragm and Buna valves allows for a variety of general purpose uses, from engine oil, automatic transmission fluids, anti-freeze solutions, water transfer and low viscosity gear lube. This pump incorporates SHURflo's advanced motor technology that includes a permanent magnet motor with ignition and thermal overload protection. 18" lead wires.

- Self-priming to 6 ft. vertical, 25 ft. horizontal
- Maximum head of 80 ft. (40 PSI)
- Liquid temperature from 40° to 185°F
- Thermal overload protection
- Geolast/Buna Elastomers
- 1.5 GPM, 4.4 amps, 40 PSI max.



ORDER NO.	DESCRIPTION	PRICE
SHU 8050305526	Standard	\$159.99
SHU 8050305626	Premium with 8' Wire and Battery Clips	\$179.99



**Self-Priming Washdown Pump**

Ideal self-priming pump for cleaning boats, general use, or for use as an aerator pump.

- Pumps 4.0 GPM
- Threaded male inlet and outlet for standard garden hose attachment
- For 12 volt D.C. systems



ORDER NO.	PRICE
ATT 115744	\$122.30



**Jabco CYCLONE Low Pressure Centrifugal Pump**

Designed specifically for marine and industrial markets. Typical applications include diesel and mild chemical transfer, hot water, primary engine cooling water and livewell bait tank circulation and deck washing.

- Heavy duty 316 stainless steel wet end components
- Quiet running
- 3,500 hour long life motor
- Rotatable head
- Anti-clog impeller design
- Long life mechanical seal
- Three year warranty
- 3/4" NPT ports



ORDER NO.	PRICE
ITT 508400012	\$247.26

**JABSCO Water Pressure Systems for Large Cruisers (30' and Larger) and Yachts**

Jabco Water Pressure Systems for Large Cruisers (30' and larger). Reliable and efficient performance is assured by the design and construction of these pumps. Belt drive and flexible mounts help reduce noise. A built-in check valve protects the pump against city water pressure. With no rotary seals to wear and the ability to run dry for extended periods without damage, these pumps are known for dependability and lack of maintenance problems. Pulsation dampeners help to absorb water hammer and smooth flow to shower and other restricted flow fixtures. Ports are for 1/2"-5/8" I.D. hose. Low amperage motors conserve battery power.



ORDER NO.	HT.	WIDTH	LENGTH	GPM	VOLTS	AMP FUSE SIZE	PRICE
ITT 369502000	8-1/2"	5-9/16"	6-9/16"	3.0	12	6/8	\$338.97



**36800 Series**

Designed specifically to supply a reliable, smooth and steady flow of water on boats with three to four water fixtures. Built-in check valve protection against city water pressure (automatic switch maintains 39 PSI pressure); pulsation dampeners to absorb water hammer, battery conserving low amperage motors, and ports sized to take 1/2" - 5/8" ID hose. Salt water system compatible for galley rinse water and deck and anchor wash down. Height 8-1/4", Width 5-1/2", Length 8-5/16".



ORDER NO.	GPM	L/min	VOLTS	FUSE SIZE	PRICE
ITT 368001000	3.3	12.5	12DC	6/8	\$495.23



**DC Vane Puppy**

The Vane Puppy operates by the rotary sliding vane principle, has Vectra rotor and vanes that are designed to handle oil or diesel fuel transfer. Pumps up to 5 1/2 GPM and transfers diesel fuel from a 55 gallon drum in 10 minutes. Self priming to 3'. Quiet. Low amp draw. The Vane Puppies are equipped with a high torque motor with ball type shaft bearings and are rated for continuous duty operation. The bronze pump has ports with 1/2" internal pipe thread and 1" external hose barb. Also supplied are port adapters for 3/4" garden hose thread. 12VDC Amp draw 8.



ORDER NO.	PRICE
ITT 186800920	\$333.57