



PAR-MAX Automatic Water System Pump For Multiple Outlet Water Systems

New Generation Par-Max multi outlet water pressure pump serves 3 or more outlets at one time. Self-priming up to 10' and is a 4 piston chamber design that delivers 3.5 GPM for smooth and quiet operation. Diaphragm design allows for extended dry running. Snap in 1/2" hose barb or 1/2" Qest ports. 12 V DC.



*Fuse not included with pump.

ORDER NO.	VOLTAGE	MAX PSI	AMP DRAW		FUSE	PRICE
			@ 10 PSI	BREAKER	BREAKER	
ITT 316200092	12 V DC	40	8		15*	\$234.05
ITT 189160040	Pressure switch					\$31.19



Accumulator Tank

A more compact pneumatic bladder tank to fit smaller systems or spaces. It smoothes faucet and shower flow by eliminating pulsations and water hammer and it also increases pump life. The tank, which is pressurized to 10 PSI, can be fine-tuned to each system. It also mounts easily in any position. Convenient snap-in barbed or optional threaded hose fittings. Working volume about 1 liter, maximum working pressure 125 psi.



ORDER NO.	PRICE
ITT 305730000	\$76.90



Smooth-Flow Water Pump Controller

- Provides smooth and quiet water flow without pulsation
- Eliminates temperature variation
- Eliminates need for space consuming accumulator tank
- Works on most water pressure pumps rated 3 - 12 amps
- Easy to install; hose and fittings included
- Runs on 12 or 24 VDC input



ORDER NO.	PRICE
ITT 317770000	\$122.66



PAR-MAX 3.5 For Multiple Outlet Water Systems

New Generation Par-Max3.5 multi outlet water pressure pump serves 3 or more outlets at one time. Self-priming up to 10' and is a 3 piston chamber design that delivers 3.5 GPM for smooth and quiet operation. Diaphragm design allows for extended dry running. Snap in 1/2" barb or 1/2" Qest ports. 12 V DC.



*Fuse not included with pump.

ORDER NO.	VOLTAGE	PRESSURE		AMP DRAW @ 10 PSI	FUSE	PRICE
		CUT-IN	CUT-OUT		BREAKER	
ITT 326000092	12 V DC	20 min	40	5	15*	\$174.24
ITT 189160040	Pressure switch					\$31.19



PAR-MAX 1.9 + 2.9 Pumps

The 1.9 GPM and 2.9 GPM are designed for vessels requiring a quiet, smooth flow, on demand pump. These new pumps are a three chamber diaphragm design offering a smooth flow and come with a built-in pulsation dampening by-pass to control unwanted cycling and noise. No need for an accumulator tank!

Product Features:

- Smooth quiet flow from .65 to 2.9 GPM
- Pressure controlled to below 25 psi
- Built in "Pulsation Eliminator"
- Runs dry without damage
- Self-priming to over 6 feet (2 meters)
- Soft rubber mounts
- Corrosion resistant
- EN ISO 8846 USCG ignition protection



ITT 312950092



ITT 313950092

ORDER NO.	GPM	VOLTAGE	PSI	PRICE
ITT 312950092	1.9	12V	35	\$113.10
ITT 313950092	2.9	12V	40	\$123.65



PAR MAX 5.0 Washdown/Livewell Pump

Par-Max5.0 is a heavy duty high pressure deck wash pump. Comes complete with Pumpgard strainer and trigger nozzle. Self-priming up to 10'. Waterproof coated sealed motor and sealed pressure switch allows mounting in exposed positions. Snap in 3/4" ports. 12 V DC. 5.0 GPM.



ORDER NO.	SHUT-OFF PSI (bar)	AMP DRAW @10 PSI	FUSE	PRICE
ITT 327000092	50 (3.5)	7	20	\$218.96
ITT 189160050	Pressure switch			\$31.19