

lubriMatic®

Heavy-Duty Barrel Pump with Multi-Direction Handle

Specifically designed for fast transfer of petroleum-based noncorrosive liquids from 15-55 gallon drums with 2" bung opening. Hand operated. Dispenses approximately 3/4 pint per stroke. Floating piston design assures positive seal and floating steel check valve drains liquid when not in use. Equipped with brass rings, Viton® seal, self-adjusting telescopic suction tube, special clamping bolt for rotating, curved spout with standard threaded male hose connector and corrosion-resistant finish. Plus rotating handle for multi-directional pumping and non-drip spout.



ORDER NO.	PRICE
LUB 55125	\$70.44

lubriMatic®

Marine Lower Unit Quart Pump 55005

Easy to use, convenient fluid pump which fits standard quart plastic bottles. Ideal for adding oil and other fluids to small engines. Easy to clean. Flexible hose gets hard-to-reach fill plugs.

55012 Adapter Fitting

Allows 55005 to be used on Yamaha, Tohatsu and Nissan lower units.

55013 Adapter Fitting

Allows 55005 to be used on Suzuki lower units.



ORDER NO.	PRICE
LUB 55005	\$16.12
LUB 55012	\$5.44
LUB 55013	\$13.47

lubriMatic®

Lower Unit Pail Pump

Designed to fit on 35 pound (5 gallon) open head pails, the pump delivers extremely high volume per stroke directly from the pail to the lower unit, fast and accurately.



ORDER NO.	PRICE
LUB 55011	\$105.72

SEI-DOG Lower Unit Standard Pump

Nylon
Standard Pump fits quart oil bottles, Flexible hose gets too hard to reach locations. Fits most motors.



ORDER NO.	DESCRIPTION	PRICE
SDG 5021501	Standard Pump	\$7.55
SDG 5021591	Yamaha Adapter	\$1.60



Automatic Transmission Fluid



ORDER NO.	CTN.	PRICE
SLL ATFQ	12	\$7.73

lubriMatic®

Lower Unit Lube Kit

Includes 1 Quart of High-Viscosity Lower Unit Gear Lube, Lower Unit Quart Pump with 3/8" Filler Fitting for Mercury, Mercruiser, OMC, Evinrude, Johnson, Volvo, Force, Gamefisher, and Honda (70 hp and up) outboard engines.



ORDER NO.	PRICE
LUB 11246	\$48.62

Coastal.

Coastal Automatic Transmission Fluid D/M

A new generation automatic transmission fluid that is approved for H specification and recommended for use in automobile and truck automatic transmissions, power-shift transmissions, and other types of service requiring an approved and licensed GM DEXRON® III (H) or Ford MERCON® automatic transmission fluid (also exceeds the requirements of DEXRON®III, DEXRON®IIE, IID, and II specifications).



ORDER NO.	SIZE	CTN.	PRICE
COA 19501	Qt.	12	\$7.87

lubriMatic®

Corrosion Control and Trailer Bearing Grease

A sophisticated lubricant developed for use in severe operating conditions caused by salt water, salt air, and atmospheric chemicals. It possesses outstanding mechanical stability, excellent water resistance and superior rust and corrosion preventive characteristics. Recommended for corrosive marine applications, boat trailer wheelbearings, or any wheel bearing subject to corrosion including disc brake wheel bearings.



ORDER NO.	SIZE	CTN.	PRICE
LUB 11400	4/3 oz.	12	\$22.05
LUB 11399	2/3 oz.	12	\$12.58

ORDER NO.	SIZE	CTN.	PRICE
LUB 11404	16 oz.	12	\$10.92