

**Permatex®**

**Ultra Black® Gasket Maker**

Fast-curing formula. Sensor-safe, low odor, non corrosive. Meets performance specs of OE silicone gaskets. Retains high flexibility, oil resistance properties through use of a patente adhesion system. Temperature range -75° F to 600° F intermittent; resists auto and shop fluids and vibration.



ORDER NO.	SIZE	CTN.	PRICE
PMT 82180	3.35 oz.	12	\$10.32

**Permatex®**

**Ultra Copper® RTV Silicone Gasket Maker**

The most advanced, high temperature RTV silicone gasket available. Sensor-safe, low odor, non-corrosive. Superior adhesion. Three times more oil resistant than conventional silicones; eight times more flexible than cut gaskets. Temperature range -75° F to 700° F intermittent; resists auto and shop fluids and vibration.



ORDER NO.	SIZE	CTN.	PRICE
PMT 81878	3 oz.	12	\$10.32

**Permatex®**

**Permanent Strength Threadlocker RED**

OEM specified. A permanent, high strength product that is applied to fasteners 3/8" to 1" (10mm to 25mm) in size before assembly. Designed for securing parts that must withstand heavy shock, vibration, or extreme chemical or environmental conditions. Localized heating and hand tools are required to separate parts.



ORDER NO.	SIZE	CTN.	PRICE
PMT 19962	6 ml	12	\$10.63

**Permatex®**

**Ultra Blue® RTV Silicone Gasket Maker**

Sensor-safe, low odor, noncorrosive. Outstanding oil resistance and joint movement values. Eight times more flexible than cork/composite gaskets; three times more oil resistant than conventional silicones. Temperature range -75° F to 500° F intermittent; resists auto and shop fluids and vibration.



ORDER NO.	SIZE	CTN.	PRICE
PMT 81724	3.35 oz.	12	\$10.25

**Permatex®**

**Penetrating Grade Threadlocker GREEN**

OEM specified as 290. A low viscosity threadlocking liquid that wicks along the threads of preassembled fasteners to secure them in place. Ideal for fasteners ranging from #2 to 1/2" (2.2 to 12mm) in size. Localized heating and hand tools are needed for disassembly.



ORDER NO.	SIZE	CTN.	PRICE
PMT 29000	6 ml.	6	\$11.63

**Permatex®**

**High Strength Threadlocker RED**

OEM specified as 271. High strength threadlocker for heavy-duty applications. Especially well-suited for permanently locking studs and press fits. Locks against vibration loosening. Requires extra effort or special tools for removal.



ORDER NO.	SIZE	CTN.	PRICE
PMT 27100	6 ml.	12	\$8.60
PMT 27140	36 ml.	6	\$44.92

**Permatex®**

**Medium Strength Threadlocker BLUE**

OEM specified as 242. All-purpose, medium strength threadlocker. Locks and seals while preventing parts loosening due to vibration. Protects threads from corrosion. Removable with hand tools for easy disassembly.



ORDER NO.	SIZE	CTN.	PRICE
PMT 24200	6 ml.	12	\$8.60
PMT 24240	36 ml.	6	\$44.92

**Permatex®**

**High Temperature Threadlocker RED**

OEM specified as 272. Hi-temp/hi-strength threadlocker for heavy-duty applications. Exclusive formulation for newer engines and high performance applications that require extreme temperature resistance. Suited for temperatures up to 450° F (232° C). Removable with heat and hand tools.



ORDER NO.	SIZE	CTN.	PRICE
PMT 27200	10 ml.	12	\$19.24